

Silver Series 2x4 Panel Light 72w



DESCRIPTION:

Touch-Plate's Panel Lights were designed to offer better security, more lumens, and higher cost savings. Our Panel Lights can offer energy savings of 70% or greater over T12, T8, and T5 traditional troffers. Our LEDs are optimal for new construction and retrofit installations.

PRODUCT FEATURES:


- Aluminum/Alloy frame for heat dissipation
- Flicker free
- Isolated driver
- Multiple mounting options
- Lifetime of 50,000 hrs or greater
- UL Listed (E471997)
- DLC Listed
 - BDPE24DUA-72wB
- 5 Year Limited Warranty

SPECIFICATIONS:

- Wattage: 72w
- Lumens: 9,000 (approx > 125lm/w)
- Equivalence: 150w HID/HPS/MH
- IP Rating: IP20
 - LED Chips: Jufei 2835
- PF: >0.90

PHYSICAL PARAMETERS:

- Dimensions
 - Length: 47.70"
 - Depth: 1.80"
 - Width: 23.70"
- Weight
 - 18.50 lbs





Silver Series 2x4 Panel Light

ORDERING GUIDE

LED Type XXX -	Lumens - Wattage XXX - XXX -	CCT XX	Voltage X
<ul style="list-style-type: none"> P24 2'x 4' Panel Light 	<ul style="list-style-type: none"> 090-072 9,000lm -72w 	<ul style="list-style-type: none"> 35 3500k 40 4000k 45 4500k 50 5000k 	<ul style="list-style-type: none"> U 100-277v

ADDITIONAL ORDERING OPTIONS

(specified at time of order)

Color


- White (Standard)
- Silver

ACCESSORIES

(specified at time of order)

- Emergency Backup
- Occupancy Sensor
- Zigbee Relay
- Zigbee Dimmer
- Zigbee Controller
- Stainless Steel Cable: 2ft / 3ft / 7ft / 10ft / 20ft
- Twist Lock Plug: 3ft / 10ft
- No Plug Extension: 3ft / 10ft
- S Hook Clip: Medium / Large
- Flush Mount Kit / Surface Mount Kit

PHOTOMETRIC



Silver Series 2x4 Panel Light

INSTALLATION INFORMATION (WIRING)


This product must be installed in accordance with National Electrical Code(NEC) and/or applicable local codes, by a qualified electrician.

DANGER - RISK OF SHOCK - DISCONNECT POWER BEFORE INSTALLATION


- Panel Light or make the necessary 'HOT' (Black or Brown), 'Neutral' (White or Blue), and 'Ground' (Green) connections in an approved junction box.

INSTALLATION INFORMATION


1. Unscrew the driver cover.




2. Connect the conduit to the driver box.





3. Make the necessary connections in the box.




4. Replace the driver cover and affix with screw.




1. Replace the existing light fixture with the LED Light Panel.




2. Use the protective brackets to safely mount the LED Panel.



Alternative 1:



Alternative 2:



Put the steel rope through the hole of the bracket and affix onto the brackets.